

06/09/25

Aqualis Deck Bright

Water based general purpose cleaner suitable for use on all coated timber and coated composite substrates including paved, tiled, concrete surfaces and BBQ areas.

- **Reduction** May be reduced up to 10 parts with water by volume.
- **Removes** Food stains, Oil, Tree Sap, Dirt and Grime, Mould, Mild oxidation.
- **Coverage Diluted** 10 m²/lt
- **Container Size** 1, 4lt, 10lt
- **Shelf Life** 12 months in original un-opened package
- **Flash Point** Non-Flammable

Uses: General purpose cleaner and brightener for all coated timber surfaces, where its unique formulation cleans and protects the coated surface. It has been designed to remove dirt and grime, tree sap, food stains, oil, and minor oxidative degradation from coated surfaces. **Deck Bright** is also useful around the house especially for removing grease and oil from, BBQ's, concrete and as a general-purpose cleaner.

APPLICATION

General Surface preparation/application

Extreme: Severe dirt and grime soiling, heavy oxidation, accumulated BBQ stains and or tree sap, mould and mildew build up.

- Dilute 1-part **Deck Bright** and up to 4 parts water by volume.
- Pre-wet timber surface with water
- Apply diluted **Deck Bright** mix by mop or spray and allow soaking in for at least 2-3 min. For stubborn stains allow 5 – 10 min soaking time.
- Scrub surface with a 'soft bristle', broom or mechanical agitator
- Thoroughly rinse off with water

Moderate to light: Removal of dirt, light oxidation, fresh BBQ stains and light build-up of tree sap. House-keeping and routine cleaning.

- Dilute 1-part **Deck Bright** to 10 parts water by volume.
- Pre-wet surface with water
- Apply diluted **Deck Bright** mix by mop or spray and allow soaking in for at least 2-3 min. For stubborn stains allow 5 – 10 min
- Scrub surface with a ‘soft bristle’, broom or mechanical agitator
- Thoroughly rinse off with water

Maintenance

It is recommended that all coated timber decking be cleaned with **Deck Bright** at least every 3 to 6 months depending on location and density of surrounding trees and native wildlife. For areas exposed to heavy soiling, frequency of cleaning will need to be at shorter intervals to maintain a natural looking timber deck.

All advice, recommendations, information, or service provided by Aqualis Coatings in relation to product manufactured or supplied by it or their use and application is given in good faith and is believed by Aqualis Coatings to be appropriate and reliable. This information may be subject to change without notice. No warranty expressed or implied is made as to its accuracy, completeness or otherwise provided that the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Aqualis by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Aqualis does not warrant the use of any competitor's products in conjunction with its own product range. Aqualis products are expected to perform as indicated provided the substrate is in good condition and has not been irreparably affected by the effects of age, biota, weather and that all preparation and application procedures are adhered to.